



EURO-EURASIA ENVIRONMENTAL SCIENCE & EDUCATION FOUNDATION

Registration No: 17247709 · Registered Non-Profit Entity: England & Wales

London, United Kingdom

research@EEEFSEF.org · www.EEEFSEF.org

Document Reference: EEESEF-RN-2026-001

Publication Date: October 25, 2026

Security Classification: PUBLIC RELEASE — Institutional Distribution Allowed

Subject Pillars: Environmental Science • Municipal Solid Waste Management • Waste-to-Energy Technologies • Environmental Protection & Public Health • Circular Economy & Resource Recovery • ESG & Sustainability • Environmental Governance & Monitoring

Municipal Waste Management and Waste-to-Energy Development in Turkmenistan

Environmental Sustainability, ESG Considerations, and Opportunities for Responsible Energy Recovery

EEEFSEF — RESEARCH NOTE (RN) SERIES

Authorship: Gelu Negreanu, Founder & Chairman — EEESEF

Published by: Euro-Eurasia Environmental Science & Education Foundation (EEEFSEF)

Classification: Public Release — For Federal Agencies, Research Councils, Universities, and Institutional Policy Reference

Independent Research Note | Vendor-Neutral | No Commercial Endorsement

Abstract

Turkmenistan's abundant natural gas resources make conventional electricity generation a distinct economic proposition from municipal waste treatment. This research note therefore examines waste-to-energy (WtE) not primarily as a response to electricity scarcity, but as one possible element of a more reliable and environmentally responsible municipal solid waste management system. It reviews the evidence available in public sources, the relevance of mature moving-grate thermal treatment technology, the role of sorting and recycling, and the environmental, social and governance (ESG) safeguards needed for any municipal decision.

The paper is a desk-based scoping study, not a waste audit, environmental impact assessment, investment proposal or project feasibility study. Local waste quantities, composition, landfill conditions, utility arrangements and technology suitability require independent confirmation. The study uses Ashgabat as a potential starting point for structured municipal assessment, while treating national replication as contingent on city-specific evidence.

Its principal conclusion is procedural: a staged municipal waste baseline, options appraisal and environmental assessment can establish whether WtE adds public value alongside prevention, reuse, recycling, biological treatment and improved final disposal. Electricity is a useful potential co-product; the environmental service remains the principal subject of decision-making.

Table of Contents

1. Executive Summary	4
2. Purpose, Scope and Research Methodology	4
3. Municipal Solid Waste Management in Turkmenistan	5
4. Environmental and Public Health Challenges	6
5. Waste-to-Energy Technologies and International Experience	7
6. Chinese WtE Technology: Maturity and Environmental Performance ..	9
7. Turkmenistan's Natural Gas and Electricity Context	10
8. Environmental, Social and Governance Assessment	10
9. Air Emissions, Water Management and Ash Disposal	12
10. Waste Hierarchy, Recycling and Circular Economy	14
11. International and Central Asian Reference Projects	14
12. Ashgabat as a Potential Initial Assessment Location	15
13. Technical, Environmental and Institutional Feasibility	17
14. Environmental Monitoring and Governance Framework	18
15. Recommendations for Turkmenistan	18
16. Opportunities for Independent Scientific Cooperation	20
17. Conclusions	21
18. References	22
Appendix A. Glossary	24
Appendix B. Indicative Municipal Assessment Checklist	24
Appendix C. Evidence and Uncertainty Register	25

1. Executive Summary

The policy question is not whether Turkmenistan needs additional electricity at any price. It is whether its municipalities could achieve a better long-term environmental outcome by strengthening collection, separation, recovery, treatment and final disposal of municipal waste. In a gas-rich economy, the electricity output of a WtE plant may contribute to a project's value, but it cannot substitute for evidence of an unmet waste-management need.

A modern moving-grate WtE facility receives mixed residual municipal waste, recovers heat through a boiler and steam turbine, and operates with dedicated air-pollution control, wastewater treatment and residue management. These systems are established internationally and widely deployed in China. Their relevance to Turkmenistan depends on the composition and reliable availability of locally collected waste, appropriate site and utility conditions, and credible governance arrangements.

The recommended starting point is a municipal baseline study, not an equipment selection. Publicly available evidence indicates official attention to a national waste-management strategy, but does not establish current Ashgabat waste tonnage or prove the absence of every operating WtE installation in Turkmenistan. These are explicit verification tasks.

A sound assessment would compare improved sanitary landfilling, recycling, organics treatment and residual-waste thermal recovery on a common environmental and financial basis. Any future WtE decision should preserve higher-value recycling and maintain accountable emissions and residue management.

2. Purpose, Scope and Research Methodology

Methodological limitation: This publication is based on publicly accessible secondary evidence. No primary waste sampling, stack measurements, site visits or municipal interviews were undertaken for this note. Technology comparisons are therefore indicative and are not a determination of project feasibility. The waste hierarchy and life-cycle perspective follow UNEP guidance [2,3,12], while emissions and residue-control topics are informed by the European Commission technical reference [4,5].

Waste streams should be differentiated before a treatment option is selected. Household refuse, market waste, commercial packaging, street sweepings, construction debris, healthcare waste and industrial residues differ in composition and legal handling requirements. A municipal WtE assessment should therefore begin with a clear definition of acceptable residual municipal solid waste and explicit exclusions for hazardous, medical and industrial waste. Mixing these categories can invalidate both combustion calculations and environmental safeguards [2,3,11].

A credible waste baseline requires more than a single daily tonnage figure. Seasonal sampling should quantify food and green waste, paper, plastics, textiles, glass, metals, inert material, moisture and lower heating value. Weighbridge records, truck counts, service-area population, collection frequency and disposal-site observations should be reconciled to identify material not captured by formal collection. Results should be reported with ranges and uncertainty rather than a single apparent national estimate [2,6].

This note is intended as a publicly distributable institutional orientation for municipal authorities, universities, researchers and environmental stakeholders. It summarises what can be established from available publications and identifies the field evidence necessary for a more detailed assessment.

The evidence base comprises Turkmenistan government announcements, UNEP and World Bank technical guidance, public Chinese municipal experience and project-reference materials supplied for context. Project concept figures are treated as scenarios rather than local measured results. No primary field sampling, engineering survey or interview programme was undertaken.

Where national statistics, operating status or project-specific data are not verified, the note uses conditional language. It distinguishes technology capability from suitability at a particular site, and technical feasibility from economic or institutional feasibility.

3. Municipal Solid Waste Management in Turkmenistan

The environmental comparison must be between plausible complete systems, not between an ideal incinerator and a poorly operated landfill. Uncontrolled disposal can cause litter, fire, smoke, odour, vectors and contaminated runoff; thermal treatment can reduce the mass and volume of residual waste requiring disposal but introduces regulated combustion emissions and ash streams. A sanitary landfill with gas management, recycling, composting or anaerobic digestion may be preferable for particular waste fractions. These pathways should be compared against the same service boundary and time horizon [2,3,6].

Turkmenistan's municipal waste system should be assessed across generation, segregation, collection, transport, processing, recycling and final disposal. The critical evidence is the amount of waste actually collected and delivered, not merely estimates of waste generated. Collection coverage, service reliability, informal recovery and seasonal variation can substantially alter the residual waste stream.

In June 2025, an official Turkmenistan government announcement reported discussions between the Ministry of Environmental Protection and the Regional Environmental Centre for Central Asia concerning a roadmap and a national waste-management strategy. This is evidence of institutional attention, not proof that a specific strategy or WtE programme has been adopted [8].

Historical international environmental reviews offer background, but should not be used as a substitute for current inspections. This note does not claim that all disposal sites are uncontrolled, that open burning is universal, or that Turkmenistan has no recycling activity. An updated municipal inventory is essential.

Historical baseline versus current evidence

The 2012 UNECE review documented both waste-management challenges and an existing mechanical-biological treatment facility in Ruhabat. It is therefore inaccurate to describe Turkmenistan as having had no treatment infrastructure. The review is a historical baseline, not proof of current landfill or collection conditions. A current municipal audit should document active facilities, their condition, actual throughput, seasonal operating constraints and the destination of recovered materials. [1]

Data architecture for a defensible baseline

A municipal material-flow balance should distinguish waste generated, collected, separately recovered, informally recovered, transferred, treated and finally disposed. Weighbridge receipts and truck-route logs are more reliable than population-based estimates alone. The study should report a range for each unmeasured flow and reconcile differences between incoming waste, recovered material and disposal tonnage. International municipal data frameworks can guide these definitions, but national figures must not be substituted for Ashgabat measurements. [6,7]

4. Environmental and Public Health Challenges

Technology screening should consider at least four routes: recycling and biological treatment of separately collected streams; sanitary landfill for residuals; moving-grate incineration with energy recovery for appropriate residual waste; and mechanical-biological treatment as a possible intermediate option. No technology is universally optimal. In particular, a city should avoid sizing a thermal facility so aggressively that future recycling improvements create a waste-feed shortage [2,3,6].

Poorly managed waste can cause litter, odour, vector attraction, local fires, uncontrolled smoke, leachate generation and land-use conflicts. Where open burning occurs, emissions are uncontained and lack the dedicated treatment available at an engineered thermal facility. The scale of such practices in Turkmenistan requires local verification.

Landfill-related concerns include methane formation from biodegradable waste, windblown material, groundwater pathways and future remediation obligations. In arid environments, water availability and the potential consequences of contaminated runoff deserve particular attention. The local significance of each pathway must be assessed through site-specific hydrogeology and operational records.

Public-health analysis should address exposure pathways and monitoring evidence rather than presume measured illness effects. The objective is to improve municipal service quality and environmental accountability while protecting nearby communities and workers.

Pathways of environmental exposure

Uncontrolled disposal can create several different exposure pathways: wind-blown litter, leachate movement, smoke from fires, dust from vehicle activity, and occupational contact during informal sorting. These impacts vary with site geology, depth to groundwater, waste composition, cover practices and prevailing wind. Consequently, any risk ranking requires site inspection and sampling rather than generic assumptions about local harm. [1,11]

Public-health and worker considerations

A credible improvement programme should address collection-worker protection, vehicle safety, traffic near receiving sites, odor complaints, pest management, and emergency response to waste fires. The social baseline should identify nearby settlements and sensitive receptors and establish a complaints mechanism before site selection is finalized. [2,11]

5. Waste-to-Energy Technologies and International Experience

Illustrative process chain — not a facility-specific engineering design



Supporting systems: odour control • leachate treatment • bottom-ash management • APC-residue containment

Figure 1. Simplified moving-grate WtE process and supporting systems; original vector schematic prepared for EESEF, based on general technical descriptions [3,4].

Modern moving-grate facilities commonly combine an enclosed tipping hall and waste bunker, crane-fed grate furnace, waste-heat boiler, steam turbine, flue-gas treatment, continuous emissions monitoring and segregated residue management. Waste may be burned with limited preprocessing, but adequate calorific value, moisture control and stable feed conditions remain essential. Electricity exported to the grid is lower than gross generation because fans, pumps, emissions controls and other auxiliaries consume power [3,4].

Waste-to-energy is a family of processes. Mass-burn moving-grate combustion is among the most established routes for mixed residual municipal waste. Other options include refuse-derived fuel production, anaerobic digestion for suitable organics, landfill-gas recovery and certain advanced thermal processes. These are not interchangeable and should be compared against the local waste stream.

In a typical moving-grate plant, vehicles deliver waste into an enclosed reception area; a bunker crane blends feedstock; controlled combustion transfers heat to a boiler; steam drives a turbine; flue gas passes through treatment stages; and bottom ash and air-pollution-control residues are managed separately. An appropriate waste acceptance protocol excludes incompatible or prohibited materials.

UNEP guidance emphasises that incineration is one possible element of integrated municipal solid waste management and should be selected through an options assessment, rather than treated as a stand-alone cure for waste-system shortcomings [2].

Stage	Function	Environmental consideration
Reception	Enclosed unloading and bunker	Odour and drainage control
Thermal treatment	Moving-grate combustion	Combustion stability
Heat recovery	Boiler and steam turbine	Energy efficiency
Flue-gas treatment	Filtration and gas cleaning	Emissions monitoring
Residues	Bottom ash and APC residues	Testing and safe disposal

Technology choice must follow waste characterization

Moving-grate combustion is a mature option for heterogeneous residual municipal waste, but its suitability depends on the lower heating value, moisture content, ash fraction and the stability of the daily supply. A seasonal sampling programme should include wet and dry periods, food waste, paper, plastics, inert materials and bulky waste. Anaerobic digestion, composting, material recovery and improved sanitary landfilling should remain in the comparison rather than being excluded at the outset. [2,3]

Energy accounting and process boundaries

Gross electricity is generated at the turbine; net exported electricity subtracts internal demand from fans, pumps, waste cranes, water treatment and pollution-control systems. Published capacities should therefore never be treated as a local electricity forecast. Heat recovery, if a viable nearby customer exists, can improve useful energy output; otherwise the study should avoid assuming district heating revenue. [3,4]

6. Chinese WtE Technology: Maturity and Environmental Performance

The opportunity cost of using waste as a fuel is different in a gas-rich electricity system. An appraisal should separately value (a) avoided environmental damage and disposal costs, (b) recovered electricity or useful heat, (c) residual ash-disposal obligations and (d) carbon emissions, including fossil carbon from plastics. The result may support WtE for waste-service reasons even where its levelized electricity cost is higher than conventional gas generation; it may also support a different waste-treatment portfolio if waste quality or governance conditions are unsuitable [2,6].

China provides an extensive body of operational experience in municipal waste incineration and power recovery. Official reporting in May 2026 stated that China had 1,137 waste incineration facilities with combined daily processing capacity of about 1.18 million tonnes at the end of 2025 [13]. This indicates technology deployment at scale, although the figures are not evidence of suitability for a particular Turkmenistan municipality.

Moving-grate systems, boilers, turbines, enclosed reception halls, leachate treatment and flue-gas cleaning are established elements of the technology. Chinese municipal experience can inform equipment specification, training and operating practice. The study intentionally does not identify or endorse any manufacturer or prospective commercial partner.

Beijing municipal reporting provides an example of published operational data on waste calorific value, generation and emissions-control practice [14]. Such reporting illustrates the kinds of performance indicators a municipality may request during technology evaluation.

Lessons from documented Chinese installations

Chinese installations provide relevant experience with high-throughput moving-grate furnaces, enclosed waste reception, heat recovery, multi-stage flue-gas treatment and operational monitoring. The Qishan environmental approval and published reporting on the Xi'an Baqiao facility may be used as documented illustrations of technology configuration, not as guaranteed performance for Turkmenistan. Vendor selection, contract terms and the identities of prospective investors fall outside this independent research note. [9,10]

What can be transferred and what must be localized

Transferable practices include controlled reception, combustion automation, maintenance planning, stack monitoring and separate residue handling. Local design still requires waste sampling, water-balance analysis, grid studies, transport planning and a permit-specific monitoring plan. This distinction is a normal engineering requirement and does not constitute an adverse assessment of any country's technology. [3,4]

7. Turkmenistan's Natural Gas and Electricity Context

An ESG screening exercise should use qualitative status categories—evidence available, evidence incomplete, significant concern, and not applicable—until field data are collected. Assigning an aggregate numerical ESG score at the desk-study stage would imply a level of precision that the available Turkmenistan evidence cannot support.

Turkmenistan's large natural-gas resource base changes the rationale for WtE. Conventional generation can provide electricity without relying on waste feedstock, so the public value of a WtE installation should be evaluated principally through avoided disposal costs, environmental improvements, reliability of treatment and possible recovery of energy.

It would be misleading to argue that WtE must be cheaper than gas-fired generation. A municipality should compare the full cost of managing residual waste under different treatment pathways, including land, collection logistics, environmental controls, residual disposal and long-term liabilities. Electricity sales may offset a portion of treatment costs but should not determine the choice in isolation.

The energy balance depends on waste calorific value, moisture content, auxiliary consumption, turbine performance and actual availability. No electricity tariff, revenue or savings figure is presented here as verified for Turkmenistan.

Why the gas-rich context changes the decision

Where gas-fired generation is established and electricity prices are low, an incinerator should not be assessed as a substitute for inexpensive power generation. The appropriate counterfactual is the cost and environmental impact of collecting, treating and disposing of the same residual waste by other means. Any electricity recovered is an offsetting benefit, but should not obscure the primary municipal service function. [2,3]

A whole-system comparison

Comparative appraisal should consider capital expenditure, annual operating and maintenance costs, residual ash disposal, replacement of pollution-control consumables, landfill land requirements, avoided open burning where documented, and recoverable materials. Because local tariffs and waste data are unverified, this paper does not present a project internal rate of return or a proposed power-purchase price. [2,6]

8. Environmental, Social and Governance Assessment

Environmental materiality should be measured at the municipal-service level. A proposed scorecard can track the proportion of collected waste weighed and characterized; separately collected recyclable and organic fractions; uncontrolled dumping and open-burning incidents; verified emissions-monitoring uptime; bottom-ash and air-pollution-control residue destinations; water withdrawal and discharge compliance; and life-cycle greenhouse-gas estimates. Each indicator needs a baseline, unit, responsible data owner, reporting frequency and independent verification method [2,4,5,11].

Social due diligence should identify the people who bear costs as well as those who receive benefits. Issues include worker exposure during waste handling and maintenance, road safety around delivery routes, informal waste-picker livelihoods, community access to grievance channels, language-appropriate consultation and emergency preparedness. Community engagement should begin before site selection is finalized and continue through commissioning and operation [2,11].

Governance should establish a traceable chain of responsibility: municipality for collection quality and service coverage; operator for permit compliance and safe plant operations; laboratory or accredited monitoring provider for measurements; regulator for enforcement; and an independent reviewer for periodic verification. Public disclosure should report exceedances, corrective actions and residue destinations, not only favorable annual averages. This approach strengthens trust without implying that EESEF would act as a regulator or project contractor [4,5,11].

The environmental dimension covers prevention of uncontrolled releases, air-quality protection, water management, residue containment, greenhouse-gas accounting and responsible land use. The social dimension covers safe employment, occupational health, community consultation, grievance mechanisms, service coverage and protection of vulnerable groups. The governance dimension covers transparent procurement, clear institutional responsibility, independent verification and public reporting.

For any facility, environmental outcomes should be assessed across the complete municipal system rather than at the plant boundary alone. For example, a well-controlled plant may still perform poorly as public policy if it diverts readily recyclable materials or leaves illegal dumping unaddressed.

An ESG scorecard can help identify missing evidence, but numerical ratings should not be assigned without a defined baseline, documented methodology and verifiable observations.

Indicative ESG decision matrix

Dimension	Assessment question	Evidence required
Environmental	Does the option reduce unmanaged waste impacts?	Baseline, EIA, monitoring
Social	Are workers and residents protected?	Consultation, safety plan
Governance	Can performance be independently verified?	Permits, reporting, audit

An operational ESG framework

Environmental indicators should include residual waste diverted from uncontrolled disposal, stack-monitoring completeness, wastewater quality, ash traceability and greenhouse-gas accounting. Social indicators should include worker training, incident rates, complaint closure and community access to information. Governance indicators should include permit compliance, public reporting, independent sampling and disclosure of corrective actions. Indicators should be measured against a documented baseline rather than promoted as guaranteed outcomes. [2,4,5]

9. Air Emissions, Water Management and Ash Disposal

The principal regulated stack pollutants include particulate matter, nitrogen oxides, sulphur dioxide, hydrogen chloride, hydrogen fluoride, carbon monoxide, heavy metals and dioxins/furans. Control trains may use selective non-catalytic or catalytic NO_x reduction, dry or semi-dry sorbent injection, activated carbon and fabric filters. The applicable permit must define measurement methods, averaging periods, calibration and reporting requirements. European BAT conclusions offer an international benchmark for technical comparison, not a substitute for Turkmenistan law [4,5].

Bottom ash and air-pollution-control residues should never be treated as a single material. Bottom ash may require ageing, testing and metal recovery before any beneficial use is considered; fly ash and filter residues often need controlled stabilization and disposal because of soluble salts and concentrated contaminants. Site plans must include a lawful destination, transport arrangements, testing protocols and long-term records for every residue stream [3,4,11].

The key air-emission topics include particulate matter, nitrogen oxides, sulphur dioxide, acid gases, heavy metals, dioxins and furans, and greenhouse gases. Engineering practice uses combustion control together with filtration, reagent systems and, where appropriate, dedicated NO_x reduction. The World Bank environmental, health and safety guidance describes such measures and the importance of stable operation [11].

Water-related systems include reception-area drainage, bunker leachate, boiler and cooling-water needs, treatment and reuse where technically suitable. Local water constraints should influence technology configuration and site selection.

Bottom ash, fly ash and air-pollution-control residues must be tracked separately. The possibility of recovering metals or using suitably tested bottom ash does not eliminate the need for classification and lawful management of hazardous residues. Independent sampling and a documented disposal pathway are central to responsible operation.

Flue-gas control train

Typical controlled incineration employs stable combustion, particulate capture, acid-gas treatment and nitrogen-oxide controls, with additional sorbents or activated carbon as appropriate for trace contaminants. Continuous monitoring is central for parameters specified by the permit, while certain pollutants require periodic laboratory testing. A stack-monitoring system does not by itself eliminate the need for calibration, quality assurance and independent inspection. [4,5]


Residues, water and the remaining landfill requirement

Bottom ash and fly-ash or air-pollution-control residues must be characterized separately; their handling pathways are not interchangeable. Some bottom ash may be processed for metals recovery or beneficial use where testing and law permit. Hazardous residues require secure treatment and disposal. A WtE plant therefore reduces but does not eliminate the need for engineered final-disposal capacity. Wastewater and leachate systems likewise need a site-specific water balance, especially in water-constrained environments. [3,4,11]

10. Waste Hierarchy, Recycling and Circular Economy

Figure 2. Illustrative municipal waste-management hierarchy; conceptual diagram prepared by EESEF.

Figure 2. Integrated municipal waste-management hierarchy



Waste prevention and reuse generally take priority over treatment of residual waste. Source separation and materials recycling should be evaluated before deciding the size of a thermal facility. Separately collected organic waste may be suitable for composting or anaerobic digestion depending on contamination, markets and collection logistics.

The appropriate role of WtE is treatment of the residual fraction that remains after practicable prevention, reuse and recovery measures. An oversized plant can create pressure to secure combustible waste and thereby weaken recycling incentives. Capacity selection should therefore be based on a forward-looking residual-waste forecast, not total gross waste generation.

The circular-economy objective is improved material productivity and lower environmental burden across the entire system. Energy recovery is a supporting measure, not a replacement for upstream waste reduction.

Avoiding conflict with recycling

The waste hierarchy gives priority to prevention, reuse and recycling, with energy recovery directed toward suitable residual fractions. Municipal procurement should avoid incentives that force recyclable material into furnaces simply to satisfy minimum tonnage. Waste contracts can define acceptable residual waste, quality ranges and periodic review of waste composition. [2,3]

Organic waste and source separation

Food and green waste may constitute a large fraction of municipal waste and can raise moisture content, lowering combustion energy recovery. Where practical, organics separation and biological treatment deserve evaluation alongside WtE. The local decision depends on collection capacity, contamination levels, markets for compost or digestate and water availability. [3,6]

11. International and Central Asian Reference Projects

International reference plants demonstrate a range of operating scales, but reference specifications are not guaranteed outcomes for Ashgabat. A 500-tonne/day moving-grate line and a 12 MW turbine are described in a public Qishan project environmental approval cited in the separate municipal concept material [9]. These figures should be treated only as an example of engineering configuration.

The Xi'an Baqiao facility is cited in public project reporting as a large-scale Chinese reference with enclosed handling and energy recovery. The study uses it as an example of technology deployment, not as evidence of project financing or environmental performance in Turkmenistan [10].

Central Asian project announcements, including a proposed Shymkent plant in Kazakhstan, indicate regional interest but must be clearly distinguished from commissioned and operating facilities. Public announcements are not a substitute for operating records [15].

Comparability of reference projects

A reference plant is informative only when its status is clear: announced, permitted, under construction, commissioned or operating. Capacity in tonnes per day, gross generator rating and net electricity exported describe different characteristics and should not be compared as equivalent measures. Chinese project documentation can support technology descriptions, while any proposed Central Asian installation should be described using its verified development status. [9,10]

12. Ashgabat as a Potential Initial Assessment Location

A practical Ashgabat pilot assessment could be organized as a twelve-month evidence programme rather than an immediate plant-sizing exercise: map existing collection and disposal systems; weigh incoming vehicles; sample representative waste across seasons; identify recyclable and organic fractions; screen land, water and grid constraints; and consult communities near candidate facilities. Only after this work should authorities compare options and determine whether a thermal treatment component merits full feasibility and environmental assessment [2,6,11].

Ashgabat could serve as a practical starting point because municipal institutions may be able to coordinate collection data, identify disposal sites and convene utility and environmental stakeholders. This is a research recommendation, not a conclusion that a specific facility is required or feasible.

The first-stage work should establish daily collected tonnage, seasonal and district variation, moisture, organic fraction, lower heating value, recycling activity, collection routes, available land, water requirements and grid access. A minimum 12-month dataset is preferable where available, supplemented by representative sampling.

A proposed capacity such as 500 tonnes/day should be regarded as a screening scenario until the municipality confirms a stable stream of suitable residual waste. The same applies to larger illustrative capacities.




Figure 3. Illustrative throughput scenarios derived from 330 operating days; not verified Turkmenistan waste volumes.




Figure 4. Illustrative electricity scenarios adapted from published reference configuration; not forecasts or guarantees.

Municipal decision questions for Ashgabat

A practical first discussion with municipal officials should ask: What is the measured daily collected tonnage? Which collection zones and transfer stations are included? How much waste is disposed at each active site? What fractions are already recycled or treated? What are the seasonal moisture and calorific-value ranges? Which authority would manage environmental permitting and public disclosure? These questions are prerequisites to a credible technology or capacity decision. [8,3]

Siting and service integration

Potential sites should be screened for road access, distance from residential receptors, prevailing winds, groundwater sensitivity, grid connection, water supply, ash transport and compatibility with existing collection routes. No particular Ashgabat site is endorsed in this note. A comparative screening matrix is more defensible than selecting land solely for its availability. [3,11]

13. Technical, Environmental and Institutional Feasibility

Feasibility is multidimensional. Technical suitability requires stable waste quantity and quality, appropriate combustion characteristics, utility connections, operability and a reliable residue outlet. Environmental feasibility requires a defensible site, impact assessment, baseline monitoring and enforceable mitigation measures.

Institutional feasibility requires a responsible public counterpart, clarity over waste collection and delivery, a lawful permitting pathway, qualified operators and mechanisms for oversight. Financial feasibility should account for the total service cost and potential funding structures, but this research note does not recommend any investor, concession or commercial arrangement.

Independent comparison should use consistent assumptions across options, including the counterfactual of improving existing collection and landfill systems. Sensitivity analysis should cover waste volumes, calorific value, downtime, electricity revenue and environmental compliance costs.

Screening inputs for Ashgabat

Parameter	Why it matters
Collected residual waste (t/day)	Facility sizing
Moisture and heating value	Combustion stability and energy
Existing recycling and organics diversion	Residual waste forecast
Water, grid and road access	Site feasibility
Permitting and residue destinations	Environmental safeguards

Stage gates for evidence-based development

A first gate establishes verified waste quantities and existing disposal practices. A second evaluates alternatives and screens environmental constraints. A third tests the technical configuration, monitoring requirements and institutional capacity. Only after those gates should detailed engineering, financing structures or concession design be evaluated by the relevant public and commercial parties. [2,3]

14. Environmental Monitoring and Governance Framework

Figure 5. Indicative monitoring and governance responsibilities; conceptual diagram prepared by EESEF.

Figure 5. Indicative environmental governance and reporting chain



Monitoring should distinguish operational process signals from independently reportable environmental results. Boiler temperature and oxygen are important for process control; continuous stack monitoring, periodic accredited sampling, ambient air monitoring where justified, water and leachate tests, and ash characterization support compliance and environmental assurance. Data should be quality-controlled, archived, reviewed against permit conditions and summarized publicly at a predictable interval [4,5,11].

A credible monitoring programme would combine continuous process and stack indicators with periodic accredited testing, waste acceptance records, water-quality sampling, ash classification and environmental incident reporting. The precise requirements must follow applicable Turkmenistan law and permit conditions, informed where appropriate by international good practice.

Municipal authorities should define ownership of data, frequency of reporting, procedures for exceedances, independent verification and public accessibility of appropriate summaries. Monitoring should begin with a baseline before any construction, enabling meaningful comparison after commissioning.

Governance should also cover complaints, corrective actions, operator training, emergency response and transparent performance review. These are institutional responsibilities rather than features supplied by equipment alone.

Monitoring responsibilities and transparency

A governance framework should identify who owns each dataset, who calibrates instruments, who verifies measurements, and how exceedances are reported and corrected. Monitoring reports should distinguish measured concentrations, applicable permit limits, averaging periods and periods of equipment downtime. A public-facing summary can report key environmental indicators without exposing confidential operational information. [4,5]

15. Recommendations for Turkmenistan

First, establish an updated municipal waste inventory and identify the present distribution of collected waste among recycling, recovery, controlled disposal and other pathways. Second, adopt an integrated options appraisal that treats prevention, reuse and recycling as core components rather than competitors to energy recovery.

Third, undertake a structured Ashgabat pre-feasibility screening with environmental, social, technical and governance criteria. Fourth, review established international WtE technologies, including Chinese moving-grate experience, using vendor-neutral performance specifications.

Fifth, develop a monitoring and public-accountability framework early in the process. Sixth, involve universities and qualified independent specialists in waste characterisation, environmental baselines and assessment of local operating conditions.




Figure 6. Proposed staged municipal evaluation sequence; a conceptual process, not an approved project schedule.



Figure 7. Photograph of a large industrial waste-to-energy facility, illustrating the scale of integrated plant buildings, utility infrastructure and auxiliary systems. Note; facility identity and operating status have not been disclosed.

The photograph in Figure 7 provides a visual reference for the physical footprint and interconnected systems that may be associated with large thermal waste-treatment installations. It is illustrative only: the photograph does not establish the design, environmental performance or suitability of any proposed facility in Turkmenistan. Site selection would require separate assessment of transport access, nearby communities, utility connections, land availability and environmental safeguards.

Prioritized municipal action sequence

The most immediately useful steps are to establish a waste-data baseline, inspect existing facilities, commission a representative composition and heating-value study, map sensitive receptors and disposal risks, and compare integrated management options. A short municipal working group could coordinate data access and identify academic institutions able to support independent sampling. These are non-binding research and planning recommendations, not project commitments. [1,2,3]

16. Opportunities for Independent Scientific Cooperation

EESEF could support non-commercial scientific exchange on waste characterization methods, environmental indicator design, independent review protocols, and educational workshops with universities and public institutions. Such activity should be documented separately from procurement, financing, construction, concession and electricity-sale arrangements. Publication of study limitations and unfavorable findings would be as important to research independence as publication of positive results.

EESEF may contribute through non-profit scientific dialogue, environmental education, knowledge exchange and independent research cooperation with universities or public institutions. Possible topics include waste-characterisation methodology, comparative environmental indicators, emissions-monitoring literacy and circular-economy education.

Such activity would be separate from plant procurement, project development, investment negotiation, construction, ownership or electricity sales. No commercial participation or endorsement is implied by this publication.

An institutional workshop could provide a useful early forum to agree data definitions and research questions before decisions on specific technologies or project structures.

Independent research contributions

EESEF could facilitate literature reviews, university cooperation, environmental-awareness activities and transparent discussion of monitoring methodology. Any future independent assessment should be separately scoped, supported by appropriate evidence and protected from influence by equipment suppliers, project investors or municipal procurement decisions. This note neither solicits a project nor offers certification of a future installation.

17. Conclusions

For Turkmenistan, the principal potential contribution of WtE is the provision of an engineered route for suitable residual municipal waste, with useful electricity as an additional output. The country's gas-rich electricity context makes this distinction especially important.

Chinese and other international experience establishes that moving-grate WtE is a mature technology category. Whether a facility should be built in Ashgabat or elsewhere depends on verified waste data, a comparison of alternatives, environmental safeguards, institutional capacity and public value.

The next responsible step is evidence gathering and an independent municipal options assessment. This research note is intended to support that discussion without pre-judging its outcome.

Limits of the present evidence

The study does not establish the current quantity or calorific value of Ashgabat's municipal waste, confirm a complete inventory of operating Turkmenistan WtE plants, identify a project site or quantify avoided emissions. These are explicit research gaps. The appropriate conclusion is that WtE merits structured consideration within an integrated waste-management strategy, subject to local evidence and comparison with other treatment options. [1,2,3]

18. References

- [1] UNECE (2012). First Environmental Performance Review of Turkmenistan, Chapter 9: Waste Management. <https://unece.org/info/publications/pub/2164>
- [2] UNEP (2019). Waste to Energy: Considerations for Informed Decision-making. <https://wedocs.unep.org/handle/20.500.11822/28413>
- [3] UNEP (2020). CCET Guideline Series: Waste-to-Energy Incineration. <https://wedocs.unep.org/handle/20.500.11822/32795>
- [4] European Commission JRC (2019). Best Available Techniques Reference Document for Waste Incineration. <https://bureau-industrial-transformation.jrc.ec.europa.eu/index.php/reference/waste-incineration-0>
- [5] European Commission (2019). Commission Implementing Decision (EU) 2019/2010: BAT Conclusions for Waste Incineration. <https://eur-lex.europa.eu/legal-content/EN/TXT/?uri=CELEX:32019D2010>
- [6] World Bank (2018). What a Waste 2.0: A Global Snapshot of Solid Waste Management to 2050. <https://documents1.worldbank.org/curated/en/697271544470229584/pdf/What-a-Waste-2-0-A-Global-Snapshot-of-Solid-Waste-Management-to-2050.pdf>
- [7] World Bank (2026 web resource). What a Waste 3.0: Global Solid Waste Management. <https://www.worldbank.org/en/publication/what-a-waste>
- [8] Government of Turkmenistan (2025). Cooperation with Regional Environmental Centre for Central Asia on waste management (official report; local verification required). <https://www.turkmenistan.gov.tm/index.php/en/post/96397/cooperation-between-turkmenistan-and-regional-environmental-center-central-asia-discussed>
- [9] Baoji Municipal Government (2025). Qishan waste-incineration project environmental approval (Chinese-language primary project reference). https://www.baoji.gov.cn/col9816/col9817/col9846/col9853/202512/t20251205_1231992.html
- [10] Xinhua (2026). Public reporting on Xi'an Baqiao WtE plant; project performance figures are secondary reports, not independently audited. <https://app.xinhuanet.com/news/article.html?articleId=20260716ca94d2d8fc894882a85765b57f3419ff>
- [11] IFC / World Bank Group (2007). Environmental, Health, and Safety Guidelines for Waste Management Facilities. <https://www.ifc.org/en/insights-reports/2000/ehs-guidelines-waste-management-facilities>
- [12] UNEP (2019). Waste to Energy: Summary for Policymakers. <https://wedocs.unep.org/handle/20.500.11822/28388>
- [13] Xinhua / State Council Information Office (2026). China targets 76% urban waste recycling rate by 2030; official 2025 waste-incineration capacity figures. https://english.scio.gov.cn/m/pressroom/2026-05/25/content_118512906.html
- [14] Beijing Municipal Commission of Urban Management (2025). Improved operational efficiency and environmental performance of Beijing waste-incineration facilities (Chinese-language municipal report). https://csglw.beijing.gov.cn/zwx/zwdtxx/zwgzdt/202503/t20250305_4026258.html
- [15] Government of Kazakhstan (2026). Construction commencement of municipal waste thermal-treatment and electricity-generation complex in Shymkent (official government announcement, Russian language). <https://gov.kz/org/mfa-xian/press/news/details/1265052>

Appendix A. Glossary

Term	Meaning
MSW	Municipal solid waste
WtE	Waste-to-energy
ESG	Environmental, social and governance
EIA	Environmental impact assessment
APC	Air-pollution control
LHV	Lower heating value
CEMS	Continuous emissions monitoring system
Residual waste	Waste remaining after practicable prevention, separation and recovery

Appendix B. Indicative Municipal Assessment Checklist

Waste data

- Daily collected tonnes by district
- Waste composition and moisture by season
- Existing recycling and organics collection
- Disposal site locations and conditions

Infrastructure

- Potential sites and buffer areas
- Grid and water access
- Transport distance and road conditions
- Ash and hazardous-residue management routes

Governance

- Responsible authorities and permits
- Public consultation procedures
- Monitoring and reporting capacity
- Operator qualifications and emergency plans

Appendix C. Evidence and Uncertainty Register

Statement	Current evidence status	Next verification
National waste strategy discussions	Official 2025 government announcement	Check subsequent adoption and implementation
Operating WtE facilities in Turkmenistan	Not definitively established in this note	Confirm through competent national authorities
Ashgabat residual waste tonnage	No verified primary dataset	Municipal weighbridge and route records
500 t/day and larger scenarios	Illustrative only	Representative sampling and feasibility
Chinese technology maturity	Documented broad deployment	Assess technical fit independently
Local electricity and treatment economics	Not assessed	Municipal comparative cost study

Publication note: This is an independent, desk-based research note. It is not an environmental approval, plant design, investment solicitation, project feasibility report, or endorsement of any supplier.

Legal Notice & Institutional Disclaimer

This research note is published by the Euro-Eurasia Environmental Science & Education Foundation (EESEF) for scientific research, environmental education and independent institutional discussion. It provides a desk-based review of municipal solid waste management, waste-to-energy technology and environmental, social and governance considerations relevant to Turkmenistan. It is not a commissioned feasibility study, an environmental impact assessment, or an assessment of a specific project site.

The analysis relies on publicly accessible literature, policy documents and illustrative international examples. Waste volumes, composition, heating value, local infrastructure, operating conditions, regulatory requirements and environmental outcomes in Ashgabat or elsewhere in Turkmenistan have not been independently measured or verified by EESEF. Illustrative throughput and electricity scenarios are not forecasts, engineering guarantees or investment projections.

This publication does not constitute engineering design, operational instructions, regulatory authorisation, procurement advice, an investment solicitation, or a recommendation to construct a particular facility. Any municipal initiative would require site-specific sampling, alternatives analysis, environmental and social impact assessment, appropriate permits, public consultation, occupational safeguards and independently verifiable monitoring arrangements.

Photographs of international facilities and explanatory diagrams, where included, are illustrative only. They do not establish the performance, environmental compliance, suitability or operating status of any proposed facility in Turkmenistan. EESEF does not endorse a manufacturer, investor, technology supplier or commercial development structure.

EESEF is an independent non-profit publisher. It makes no warranty that the information is suitable for any particular project and accepts no responsibility for third-party technical, commercial, financial or regulatory decisions made without independent professional review.

Sign-Off and Closing Block

APPROVAL FOR PUBLICATION

This research note has been reviewed and approved for publication by the Euro-Eurasia Environmental Science & Education Foundation (EESEF).

Gelu Negreanu

Founder & Chairman

Euro-Eurasia Environmental Science & Education Foundation (EESEF)

Date of Publication: October 25, 2026

EESEF Company No. 17247709

Registered in England & Wales

© 2026 EESEF. All rights reserved.

EESEF · Company No. 17247709 · Registered in England & Wales · www.EESEF.org · research@EESEF.org